

StreetStick Specification sheet

We reserve the right to alter specification without prior notice.

CureStick Specification

Lumen output (lm)	>5300 @ 6000K, > 5000 @ 4000K, >4600 @3500K, >4200 @ 3000K
System efficiency (lm/W)	>115 @ 6000K, >105 @ 4000K, >100 @ 3500K, >95 @3000K
CCT Correlated Color temperature	6000K, 4000K, 3500K, 3000K based on customer request and MOQ
Lifetime	More than 50,000 hours (L80, drop to 80% light flux)
Supply voltage / current	~ 36V CD, CC mode / 1,1A
Power consumption	< 50W, depending on selected external power supply
Light intensity control	1-10V, Astro DIM, 3,4 Semne, etc, based on customer request

Environmental

Ambient Temperature	0-40°C
IP Class	IP67
Storage Temperature	-40 to 90°C
Relative humidity	Up to 90%

Physical

Housing color	Aluminum natural (anodized)
Installation	2 x M8 screw, 60-62 mm
Dimensions (max)	800 x 100 x 150 mm, Main body height only 20 mm
Weight	6 kg
Warranty period	3 years for main fixture



FuturoLighting Ltd.
Headquarter Address: N. Teslu 5,
92101 Piestany, Slovakia

Company Identification Number: 45 981 809
VAT: SK2023166783

e-mail: info@fulit.eu
Phone: +421 948 388 317
WEB: <http://www.fulit.eu>